

DOMINATOR 30

AT A GLANCE







One piece top-adaptor reduces internal parts. No make up required. External N.R.V. for easy maintenance.

Revised chamber volumes and cycle timing to optimize performance.

Simplified piston geometry for improved balance and location within the cylinder.

Heavy duty cylinder for extended hammer life.

DOMINATOR 30


The Dominator 30 hammer is a high performance hammer for medium to hard rock conditions. This hammer has no internal liner which allows a larger piston diameter for greater blow energy. The Dominator 30 has fewer parts than any other 3 inch hammer in the market. This allows for easy maintenance and servicing with only a few simple tools required.

Suitable for operation at air pressures of 100 - 350 psi (7 - 24 bar).

Drilling diameters of 90mm - 104mm (3 1/2 - 4 1/8").

Available Shanks

I.R 3.5



Figures are based on theoretical data



| Dominator 30 | | |
|---|--|--|
| 600424 | | |
| IR 3.5 | | |
| 2 % Api Reg Pin | | |
| 63 mm (2.480") | | |
| 23 kg | | |
| 81 mm (3 ³ / ₁₆ ") | | |
| 832 mm (32 ³ / ₄ ") | | |
| 150 kg (330 lbs) | | |
| 300 kg (660 lbs) | | |
| | | |

| Hammer Type Shank | Dominator 30 I.R 3.5 600424 | Maintenance Kits | | |
|----------------------|-----------------------------------|------------------------|-------|--|
| Model Number | | Service Kit Repair Kit | | |
| Item | Description | SK81 | RK136 | |
| 1 | Thread Protector | - | - | |
| 2 | Top-Adaptor | - | - | |
| 3 | O'Ring | 2 | 2 | |
| 4 | N.R.V. | - | 1 | |
| 5 | N.R.V. Spring | 2 | 2 | |
| 6 | N.R.V. Housing | | - | |
| 7 | Disk Springs | 2 | 2 | |
| 8 | Thrust Washer | - | - | |
| 9 | O'Ring | 2 | 2 | |
| 10 | Air Distributor | | 1 | |
| 11 | Washer | - | - | |
| 12 | Snap Ring | 2 | 2 | |
| 13 | Piston | - | _ | |
| 14 | Cylinder | - | - | |
| 15 | Snap Ring | 2 | 2 | |
| 16 | Bit Retaining Rings | | 1 | |
| 18 | Chuck Spacer | 1 | 1 | |
| 19 | Chuck | - | 1 | |
| 20 | End Cap | - | - | |

| Drill Bits | | | | | | | | | |
|------------|----------|---------|--------|----------------|---------------|--------|--|--|--|
| Part | Diameter | | Face | Buttons | | Weight | | | |
| Number | mm | Inch | Design | Туре | QTY/DIA | (kg) | | | |
| I.R 3.5 | | | | | | | | | |
| 650622 | 90 | 3 1/2 | Convex | Semi-Ballistic | 13 x 11 mm | 3.8 | | | |
| 650609 | 95 | 3 3/4 | Convex | Semi-Ballistic | 15 x 11 mm | 4.0 | | | |
| 650621 | 100 | 3 15/16 | Convex | Domed | 15 x 11 mm | 4.5 | | | |
| 650624 | 104 | 4 1/8 | Convex | Domed | 8x13mm/8x11mm | 4.9 | | | |

Additional drill bit configurations are available upon request



